


Overview of our technology



Look here for the newest updates,
specifications and more detailed descriptions:

Model

3400

5000

6000

Motor

Type Electric motor	Asynchronous motor	Asynchronous motor	Asynchronous motor
Power (kW)	160	200	280

Loading heights

Loading heights (mm)	Hook: 2,396 Trailer: 2,996
Discharge heights (mm, 10°-35°)	Hook: 1,520-3,842 Trailer: 1,929-4,250

Shredding unit

Drum drive	hydraulic	hydraulic	hydraulic
Drum rpm	max. 32	max. 33	max. 39
Drum length (mm)	2,820	2,820	2,820
Drum diameter (mm)	610	610	610

Dimensions in transport position/working position (conveyor belt 35°)

Hook – L x B x H (mm)	7,290 x 2,500 x 2,766 12,292 x 3,290 x 3,842
Trailer – L x B x H (mm)	9,065 x 2,549 x 3,367 13,497 x 3,290 x 4,250

Weight (dependent on equipment)

Hook (t)	21.7	22	22.3
Trailer (t)	24	24.3	24.6

Throughput (dependent on material)

Throughput	up to 55	up to 80	up to 100
------------	----------	----------	-----------

Hook (hook lift chassis)



Trailer (3-axle trailer)

