

TECHNICAL SPECIFICATIONS

Overview of our technology

Look here for the newest updates, specifications and more detailed descriptions:



Model	4510	6210
Engine		
Manufacturer	Caterpillar	Caterpillar
Power (kW/HP)	340/462	430/585
Material feed		
Feed table L x W (mm)	4,155 (3,600 active) x 1,430	4,155 (3,600 active) x 1,430
Feed table height (mm)	2,250	2,250
Number of feed drums	1 horizontal	1 horizontal
Feeder opening H x W (mm)	850 x 1,430	850 x 1,430
Shredding unit		
Drum diameter x drum width (mm)	1,100 x 1,550	1,100 x 1,550
Tools	32 free swinging tools or 32 fixed tool holders	32 free swinging tools or 32 fixed tool holders
Drum rpm	460/912	460/912
Material discharge		
Conveyor belt, width (mm)	1,200	1,200
Discharge height (35°, mm)	Trailer: 4,500 Track: 4,380	Trailer: 4,500 Track: 4,380
Dimensions in transport position/working position (conveyor belt 35°)		
Transport position L x W x H (mm)	Trailer: 9,980 x 2,497 x 3,700 Track: 8,390 x 2,497 x 3,580	Trailer: 9,980 x 2,497 x 3,700 Track: 8,390 x 2,497 x 3,580
Working position L x W x H (mm)	Trailer 2-axles: 13,347 x 2,497 x 4,500 Track: 12,469 x 2,497 x 4,380	Trailer 3-axles: 13,347 x 2,497 x 4,500 Track: 12,469 x 2,497 x 4,380
Weight (t)	Trailer: -19 Track: -21	Trailer: -21 Track: -23
Throughput (dependent on material)		
Throughput (m ³ /h)	up to 250	up to 300

Axtor 4510 Trailer



Axtor 6210 Trailer



Axtor 4510/6210 Track

