



# Cat<sup>®</sup> 962

## Wheel Loader

**The Cat<sup>®</sup> 962 Wheel Loader brings premium performance with simple-to-use technologies as a standard offering, boosting operator efficiencies and delivering consistent high bucket fill factors resulting in up to 10% increased productivity.\* Extended service intervals lower maintenance costs by up to 30%.\* This machine is designed to meet emission standards without interrupting operation. Improved performance, reliability, durability, and versatility result in a machine that is better built to meet your needs.**

**\*Compared to previous Cat model**

### Proven Reliability

- Cat C7.1 engine<sup>†</sup> offers high power density with a combination of proven electronics, fuel, and air systems.
- Equipped with automatic Cat regeneration system, Cat Clean Emissions Module (CEM) with Diesel Particulate Filter (DPF), and Diesel Exhaust Fluid (DEF) tank and pump.
- Features an electric fuel priming pump, fuel-water separator, and secondary fuel filter.
- Thorough component design and machine validation processes result in unmatched reliability and uptime.

### Work in Comfort in the All New Cab

- Next-generation, easily adjustable seat and suspension for improved operator comfort. It comes in three trim levels and can be equipped with a 4-point harness (kit).
- Increased legroom and adjustable seat controls for increased comfort and efficiency.
- Automatic air conditioning system keeps the cab temperature as desired.
- New in-cab dashboard and high-resolution touch display(s) are easy to use, intuitive, and user friendly.
- Sound suppression, seals, and viscous cab mounts decrease noise and vibration for a quieter work environment.
- The standard HMU steering wheel provides precision control, resulting in excellent comfort and accuracy. An optional seat-mounted electro-hydraulic joystick steering system (replaces the HMU steering wheel) is also available in many regions.
- The next generation of ride control works as a shock absorber, improving ride quality over rough terrain.

### Durability

- Heavy-duty transmission and axles designed to handle extreme applications.
- Automatic countershaft powershift (5F/3R) transmission features durable, long-lasting components.
- Full-flow hydraulic filtration system with additional kidney-loop filtration improves hydraulic system reliability and component life.
- Next Generation implement pump increases flow at lower engine speeds and improves hydraulic response.

### Smart Machine for Efficient Operation

- Standard Cat technologies to monitor, manage, and enhance your jobsite operations.
  - Cat Payload with Assist provides accurate weighing\*\* of the bucket payloads. Data is displayed in real time to improve productivity and loading accuracy with manual tip-off.
  - Product Link™ wirelessly connects the machine to the office, giving you access to production and essential health information needed to make timely, fact-based decisions to help you better run your business.
  - New Autodig allows the operator to fully automate bucket loading to improve fill factors and loading time.
  - Auto Set Tires promotes proper loading technique, significantly reducing tire slip and tire wear.
- Optional Cat Advanced Payload with Assist:
  - Tip Off Assist automatizes load adjustment of the final bucket to match hauling unit target.
  - Enhanced lists management, site integration, and extended scale features to help manage and improve productivity and profitability of operations.
- Optional Cat Productivity subscription provides detailed and comprehensive actionable information to help you manage and improve the productivity and profitability of your operations.

**\*\*Not legal for trade.**

<sup>†</sup>Cat engine meets U.S. EPA Tier 4 Final, EU Stage V, Korea Tier 5, India CEV Stage V and Japan 2014 emission standards.



# Cat® 962 Wheel Loader

---

## Achieve Greater Fuel Efficiency & Productivity

- New Autodig with Auto Set Tires for consistent high bucket fill factors deliver up to 10% more productivity compared to previous Cat model.
- 5-speed transmission and lock-up clutch torque converter, power trains deliver smooth shifting, fast acceleration, and speed on grade for greater performance and fuel efficiency.
- Single clutch and lock-to-lock shifting for faster acceleration and speed on grades.
- Z bar\* linkage provides high breakout force at ground level.
- Optimized Z bar\* linkage offers parallel lift capability for precise work tool control.
- Performance Series Buckets utilize a system-based approach to balance bucket shape against the machine's linkage, resulting in higher fill factors and better material retention when compared with other buckets of the same rated capacity.
- Application Profiles optimize machine settings for different applications at one push of a button.
- Job Aids help operators improve and optimize their operating skills.
- Automatic engine idle shutdown system significantly reduces idle time, overall operating hours, and fuel consumption.
- Deeply integrated engine, power train, and hydraulic systems deliver unmatched productivity and fuel efficiency.
- Standard front manual differential locks and optional auto front and rear differential locks improve traction, resulting in increased productivity while reducing tire scuffing for reduced operating costs.
- Fusion™ Quick Coupler allows for easy tool changes without leaving the cab, letting the machine move quickly from task to task.

*\*Not all configurations available in all regions, subject to availability*

## Reduced Maintenance Time and Costs

- Extended fluid and filter change intervals reduce maintenance costs by up to 30%.\*\*
- Convenient access to hydraulic and electrical service centers for easy ground-level servicing.
- Remote Troubleshoot can connect the machine to the dealer service department to help diagnose problems quickly so you can get back to work.
- Remote Flash works around your schedule to ensure your machine's software is up to date for optimal performance.
- The Cat App helps you manage fleet location, hours, and maintenance schedules; it also alerts you for required maintenance and allows you to request service from your local Cat dealer.
- One-piece tilting hood makes engine compartment access fast and easy.
- Optional Integrated Autolube extends component and service life.

*\*\*Parts and fluids only*

## Safety Features

- Rear-vision camera enhances visibility behind the machine, helping you work safely and confidently.
- Cab access with wide door, optional remote door opening, and inclined steps add solid stability.
- Floor-to-ceiling windshield, large mirrors with integrated spot mirrors, and rear-vision camera provide industry leading all-around visibility.
- Computerized monitoring system includes several warning indicators.
- Monitored seat belt is standard and can be enhanced with an optional exterior indicator.
- Optional multiview (360°) vision system helps the operator monitor the surroundings of the machine at all times.
- Optional Cat Detect radar technology enhances awareness by monitoring the working environment and alerts operators to hazards.
- Optional access light and under-hood service light system to provide illuminated access to the machine and daily checks even in the dark.

## Purpose-built Specialty Configurations

- Application-specific arrangements direct from the factory for optimized performance and added durability in the toughest applications, including:
  - Industrial and waste models feature guarding and reinforcement necessary for work in transfer stations, recycling depots, scrap yards, and demolition sites.
  - Forestry model increases lift and tilt capacities for efficient and productive log and chip handling in paper, pellet, and sawmills.

## Standard and Optional Equipment

Standard and optional equipment may vary. Consult your Cat dealer for details.

	Standard	Optional		Standard	Optional
<b>OPERATOR ENVIRONMENT</b>			<b>POWER TRAIN (Continued)</b>		
Cab, pressurized, sound suppression	✓		Service brakes, hydraulic, fully enclosed wet disc, wear indicators, Integrated Braking System (IBS)	✓	
Door, remote opening system		✓	Park brake, caliper on front axles, spring applied–pressure released	✓	
EH implement controls, parking brake	✓		<b>HYDRAULICS</b>		
HMU steering wheel	✓		Implement system, load sensing with variable displacement piston pump	✓	
Steering, joystick		✓	Steering system, load sensing with dedicated variable displacement piston pump	✓	
Entertainment radio		✓	Ride control, dual accumulators	✓	
CB radio ready		✓	3 <sup>rd</sup> and 4 <sup>th</sup> auxiliary functions with ride control		✓
Seat, cloth, air suspension	✓		Oil sampling valves, Cat XT™ hoses	✓	
Seat, suede/cloth, air suspension, heated		✓	Quick coupler control		✓
Seat, leather/cloth, air suspension, heated/cooled		✓	<b>ELECTRICAL</b>		
Touchscreen display	✓		Starting and charging system, 24V	✓	
Visibility: mirrors, rear-vision camera	✓		Starter, electric, heavy duty	✓	
Multiview (360°) vision system		✓	Cold start, 120V or 240V		✓
Cat Detect rear radar system		✓	Lights: halogen, 4 work lights, 2 front roading lights with turn signals, 2 rear-vision lights	✓	
Dedicated rearview screen		✓	Lights: LED		✓
Mirrors, heated		✓	Warning beacon		✓
Air conditioner, heater, defroster (auto temp, fan)	✓		Reversing strobe lights		✓
Sun visor, front and rear, retractable	✓		<b>MONITORING SYSTEM</b>		
Window cleaning platform, front	✓		Front dash with analog gauges, LCD display, and warning lights	✓	
Window, front, laminated	✓		Primary touchscreen monitor (Cat Payload, quad screens, machine settings & messages)	✓	
Windows, front, heavy duty		✓	<b>LINKAGE</b>		
Full cab window guard		✓	Parallel Lift, Z-bar*	✓	
<b>ON-BOARD TECHNOLOGIES</b>			Standard lift, Z-bar*		✓
Cat Payload scale	✓		High lift available with both linkages*		✓
Autodig with Auto Set Tires	✓		Kickouts: lift and tilt	✓	
Operator ID & machine security	✓		<b>ADDITIONAL EQUIPMENT</b>		
Application Profiles	✓		Cat Autolube system		✓
Job Aids	✓		Fenders, extensions or roading		✓
Controls Help and eOMM		✓	Guards: power train, crankcase, cab, cylinders, rear		✓
Cat Advanced Payload		✓	Biodegradable hydraulic oil		✓
Cat Payload Printer		✓	High-speed oil change system		✓
<b>POWER TRAIN</b>			Rear cab access		✓
Cat C7.1 engine	✓		Toolbox		✓
Electric fuel priming pump	✓		Wheel chocks		✓
Fuel-water separator and secondary fuel filter	✓		Secondary steering system, electrical**		✓
Engine, air precleaner	✓		<b>SPECIAL CONFIGURATIONS</b>		
Turbine, air precleaner		✓	Auxiliary Counterweight		✓
Radiator, high debris		✓	Waste and industrial		✓
Cooling fan, reversible		✓	Forestry		✓
Axles, front differential lock	✓		Corrosion resistant		✓
Axles, auto differential locks front and rear		✓			
Axles, ecology drains, AOC ready, extreme temperature seals		✓			
Axles, oil cooler		✓			
Transmission, countershaft, automatic powershift	✓				
Torque converter with lock-up	✓				

# Cat® 962 Wheel Loader

## Technical Specifications

Engine		
Engine Model	Cat C7.1	
Engine Power @ 2,100 rpm – ISO 14396:2002	201 kW	269 hp
ISO 14396:2002 (DIN)	273 mhp (PS)	
Gross Power @ 2,100 rpm – SAE J1995:2014	203 kW	273 hp
SAE J1995:2014 (DIN)	277 mhp (PS)	
Net Power @ 2,100 rpm – ISO 9249:2007, SAE J1349:2011	187 kW	251 hp
ISO 9249:2007 (DIN)	255 mhp (PS)	
Engine Torque @ 1,400 rpm – ISO 14396:2002	1245 N·m	918 lbf·ft
Gross Torque @ 1,400 rpm – SAE J1995:2014	1256 N·m	926 lbf·ft
Net Torque @ 1,400 rpm – ISO 9249:2007, SAE J1349:2011	1176 N·m	867 lbf·ft
Displacement	7.0 L	

- Cat engine meets U.S. EPA Tier 4 Final, EU Stage V, Korea Tier 5, India CEV Stage V and Japan 2014 emission standards.
- The net power advertised is the power available at the flywheel when the engine is equipped with fan, alternator, air cleaner, and aftertreatment.
- Cat diesel engines are required to use ULSD (ultra-low sulfur diesel fuel with 15 ppm of sulfur or less) or ULSD blended with the following lower-carbon intensity fuels up to:
  - 20% biodiesel FAME (fatty acid methyl ester)\*
  - 100% renewable diesel, HVO (hydrogenated vegetable oil) and GTL (gas-to-liquid) fuels

Refer to guidelines for successful application. Please consult your Cat dealer or "Caterpillar Machine Fluids Recommendations" (SEBU6250) for details.

\* Engines with no aftertreatment devices can use higher blends, up to 100% biodiesel.

## Weight

Operating Weight 20 171 kg 44,469 lb

- Weight based on a machine configuration with Parallel lift z-bar linkage, Bridgestone 23.5R25 VJT L3 radial tires, full fluids, operator, standard counterweight, ride control cold start, roading fenders, Product Link, front manual differential/open rear axles, power train guard, secondary steering, sound suppression, and a 3.3 m<sup>3</sup> (4.3 yd<sup>3</sup>) general purpose bucket with BOCE.

## Transmission

Speed	km/h	mph	Speed	km/h	mph
Forward 1	6.9	4.3	Reverse 1	6.9	4.3
Forward 2	12.0	7.5	Reverse 2	12.0	7.5
Forward 3	19.3	12.0	Reverse 3	25.7	16.0
Forward 4	25.7	16.0			
Forward 5	39.5	24.5			

- Maximum travel speed in standard vehicle with empty bucket and standard L3 tires with 787 mm (31 in) roll radius.

## Sound

Operator Sound Pressure Level (ISO 6396:2008)	70 dB(A)
Exterior Sound Power Level (ISO 6395:2008)	107 dB(A)
Operator Sound Pressure Level (ISO 6396:2008)*	69 dB(A)
Exterior Sound Power Level (ISO 6395:2008)**	104 dB(A)

\*Including countries that adopt the EU and UK Directives.

\*\*European Union Directive 2000/14/EC and UK Noise Regulation 2001 No. 1701

## Air Conditioning System

The air conditioning system on this machine contains the fluorinated greenhouse gas refrigerant R134a (Global Warming Potential = 1430). The system contains 1.6 kg (3.5 lb) of refrigerant which has a CO<sub>2</sub> equivalent 2.288 metric tonnes (2.522 tons).

## Bucket Capacities

Bucket Range 2.67-9.90 m<sup>3</sup> 3.5-13.0 yd<sup>3</sup>

## Operating Specifications

Static Tipping Load – Full 40° Turn:

With Tire Deflection	11 734 kg	25,869 lb
No Tire Deflection	12 487 kg	27,529 lb

Breakout Force 189 kN 42,489 lbf

- For a machine configuration as defined under "Weight."

- Full compliance to ISO 14397-1:2007 Sections 1 thru 6, which requires 2% verification between calculations and testing.

## Service Refill Capacities

Fuel Tank	259.5 L	68.6 gal
DEF Tank	15 L	4.0 gal
Cooling System	54 L	14.3 gal
Crankcase	21 L	5.5 gal
Transmission	43 L	11.4 gal
Differentials and Final Drives – Front	43 L	11.4 gal
Differentials and Final Drives – Rear	43 L	11.4 gal
Hydraulic Tank	97 L	25.6 gal

## Hydraulic System

Implement System:

Maximum Pump Output (2,340 rpm)	322 L/min	85 gal/min
Maximum Operating Pressure	29 300 kPa	4,250 psi
Hydraulic Cycle Time – Total	9.4 seconds	

## Dimensions

	Standard Lift		High Lift	
Height to Top of Hood	2692 mm	8'9"	2692 mm	8'9"
Height to Top of ROPS	3453 mm	11'3"	3453 mm	11'3"
Ground Clearance	351 mm	1'1"	351 mm	1'1"
Wheelbase	3350 mm	10'11"	3350 mm	10'11"
Overall Length (without bucket)	7263 mm	23'10"	7657 mm	25'2"
Hinge-Pin Height at Carry Height	674 mm	2'2"	776 mm	2'6"
Hinge-Pin Height at Maximum Lift	4223 mm	13'10"	4511 mm	14'9"
Lift Arm Clearance at Maximum Lift	3459 mm	11'4"	3612 mm	11'10"
Rack Back at Maximum Lift	55 degrees		56 degrees	
Rack Back at Carry Height	51 degrees		48 degrees	
Width over Tires (Loaded)	2825 mm	9'4"	2825 mm	9'4"
Tread Width	2140 mm	7'0"	2140 mm	7'0"

- All dimensions are approximate and based on machine equipped with 3.3 m<sup>3</sup> (4.3 yd<sup>3</sup>) general purpose bucket with BOCE and Bridgestone 23.5R25 VJT L3 radial tires.



オフロード用2014年  
基準適合

AEXQ3443-00 (08-2022)

Build Number 14A

(N Am, Europe, Japan, S Korea, India, Turkey)

For more complete information on Cat products, dealer services, and industry solutions, visit us on the web at [www.cat.com](http://www.cat.com).

Materials and specifications are subject to change without notice. Featured machines in photos may include additional equipment. See your Cat dealer for available options.

© 2022 Caterpillar. All Rights Reserved. CAT, CATERPILLAR, LET'S DO THE WORK, their respective logos, Fusion, Product Link, XT, "Caterpillar Corporate Yellow", the "Power Edge" and Cat "Modern Hex" trade dress as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.

