

PRODUCT SPECIFICATIONS FOR 3612



Maximum Power	3700 kW
Maximum Torque	41822 Nm @ 800 rpm
Rated Speed	750-1000 rpm
Minimum Power	2980 kW
Emissions	Non-Certified
Engine Configuration	V-12, 4-Stroke-Cycle Diesel
Bore	280 mm
Stroke	300 mm
Displacement	221.7 l
Aspiration	Turbocharged Aftercooled
Rotation from Flywheel End	Counterclockwise
Aftertreatment	-
Length	4562 mm
Width	1704 mm
Height	3231 mm

© 2014 Caterpillar Inc. All rights reserved. CAT, the CAT logo, and 3612 are trademarks of Caterpillar Inc. in the United States and other countries.

3612 STANDARD EQUIPMENT

AIR INLET SYSTEM

Aftercooler core, corrosion resistant coated (air side)

Air cleaner. Regular duty, dry, panel type with service indicators, turbocharger, jacket water aftercooled.

Turbocharger, rear mounted

Jacket water aftercooled

CONTROL SYSTEM

Governor, RH, 3161 with self contained synthetic oil sump

Air-fuel ratio control

Mechanical speed control, without torque control

Governor control

Positive locking

COOLING SYSTEM

Thermostats and housing

Jacket water pump, centrifugal

EXHAUST SYSTEM

Exhaust manifold, dry

FLYWHEELS AND FLYWHEEL HOUSING

SAE No. 00 flywheel

183 flywheel teeth

SAE No. 00 flywheel housing

FUEL SYSTEM

Fuel filter, with service indicators, cartridge type with RH service

Fuel transfer pump

INSTRUMENTATION

Instrument Panel. RH

Engine oil pressure gauge
Fuel pressure gauge
Oil filter differential gauge
Jacket water temperature gauge
Service meter, electric
Tachometer

LUBE SYSTEM

Crankcase breather, top mounted
Oil cooler
Oil filler
Oil dipstick
Oil pump
Oil filter, cartridge type with RH service
Shallow oil pan

MOUNTING SYSTEM

Rails, mounting, engine length, 254 mm (10 in), industrial-type, C-channel.

POWER TAKE OFF

Accessory drive, upper RH
Front housing, single sided

PROTECTION SYSTEM

Junction box
Manual shutoff, RH
Safety shutoff protection, energized to shutdown
Low oil pressure, low idle 69 kPa (10 psi); high idle 207 kPa (30 psi)
Water temperature
Overspeed
3161 governor solenoid energized to shutdown

STARTING SYSTEM

Starting switch

GENERAL

Vibration damper
Lifting eyes
Paint: Caterpillar yellow, with optional colors available at request

